

Indoor Unit		يونيٲ داخلي						FDYB20CXV1R	FDYB25CXV1R	FDYM30EXV1R	FDYM40EXV1R	FDYB50CXV1R	EDM60JEV1K
Nominal Cooling Capacity		Btu/h	1.5 Tn	2 Tn	2.5 Tn	3 Tn	4 Tn	5 Tn					
Nominal		Amperage A مصرفي	18,500	24,500	30,800	36,900	48,000	56,000					
EER		W/W	5.59	10.4	13.6	13.9	6.78	7.81					
		Btu/h/W	3.47	2.77	2.74	2.92	2.83	2.90					
External static pressure		Pa	11.86	9.46	9.33	9.97	9.66	9.89					
Sound Pressure level		dB(A)	265/257/246	286/274/242	448/424/353	471/448/415	920/770/670	970/870/750					
Dimension		mm	561/544/522	607/581/512	950/900/750	1200/1100/1020	1600/1330/1270	2060/1850/1590					
Weight		Kg	20/19/15	20/18/11	50/50/50	50/50/50	78/59/39	69/49/29					
Power supply		V/Ph/Hz	40/39/38	41/40/38	45/44/39	46/45/44	55/53/52	58/56/54					
		Phase/frequency/voltage	261 x 11065 x 411	261x1200x411	292x1228x420	292x1228/420	378x1299x541	378x1499x541					
			24	26	32	32	54	62					
			220-240/1/50										

Outdoor Unit		يونيٲ خارجي						R20CGXV1	R25CGXV1	RD30JEV1K	RD40JEV1K RD40JEV1K	R50DGXV1	RD60JEV1K
Air Flow		l/s	1.5 Tn	2 Tn	2.5 Tn	3 Tn	4 Tn	5 Tn					
Air Flow		CFM	788	827	807	2100	1710						
Sound pressure level		dB(A)	1670	1752	1712	4450	3630						
Dimension		mm	52	56	56	68	67	66					
weight		Kg	651x855x328	753x855x328	852x1030x400	852x1030x400	852x1030x400	852x1030x400					
Pipe connection		Liquid	47	57	70	88	105	108					
		Gas	6.35			9.52		12.7					
			1/4			3/8		1/2					
Compressor		Type	15.88	15.88			19.05						
		Min.~Max.	5/8	5/8			3/4						
Operating range		°CDB	Rotary		Twin Rotary		Scroll						
Power supply		V/Ph/Hz	220-240/1/50		220-240/1/50		380-415/3/50						